

446

RESURVEY OF THE SUBDIVISION OF T. 19 S., R. 56 E.

Chains

from which
 A limber pine, 12 ins. diam., bears S. 45° E.;
 30 lks. dist., mkd. $\frac{1}{4}$ S18BT.
 A limber pine, 6 ins. diam., bears N. 25° W.,
 30 lks. dist., mkd. $\frac{1}{4}$ S7BT.

Continue descent along N. slope.

42.60 Canyon, 42 ft. below $\frac{1}{4}$ sec. cor., drains S. 70° W., timber becomes less dense; asc. along steep S. slope covered with sliderock.

51.60 Small draw, drains S. 10° E. about 5 chs. to canyon; asc. steep SE. slope.

57.40 Slope changes to S.

61.30 Spur, 322 ft. above canyon, projects S. 80° W. from N. 70° E.; desc. along NW. slope, through dense timber, 119 ft. to the cor.

68.84 Intersect the W. bdy. of the township.

Set an iron post, 3 ft. long, 2 ins. diam., 15 ins. in the ground to bedrock, and in a large mound of stone to top of post, for the closing cor. of secs. 7 and 18, with brass cap mkd.

T19S

T19S

S7 C

S13

S18 C

R55E

R56E

1933

from which
 A cattail pine, 14 ins. diam., bears S. 53° E.,
 23 lks. dist., mkd. T19SR56ES18CCBT.
 A cattail pine, 4 ins. diam., bears N. 18 $\frac{1}{2}$ ° E.,
 84 lks. dist., mkd. T19SR56ES7CCBT.

From the point of intersection, the cor. of secs. 12 and 13, T. 19 S., R. 55 E., heretofore described, bears N. 0°32' W., 18.77 chs. dist.

From the same point, the $\frac{1}{4}$ sec. cor. of sec. 13, T19S., R. 56 E., heretofore described, bears S. 0°32' E., 20.65 chs. dist.

Land, rough mountainous.
 Soil, shallow loam; 3rd rate.
 Timber, cattail and limber pine.
 Undergrowth, young timber.

From the cor. of secs. 7, 8, 17, and 18.

N. 0°03' W., bet. secs. 7 and 8.

Over mountainous land, through dense timber; asc. along W. slope.