

RESURVEY OF THE SUBDIVISION OF T. 19 S., R. 56 E.

Chains	
.60	N. edge of bottom of canyon, bears S. 80° W. and N. 80° E.; asc. abrupt S. slope.
2.00	Slope changes to SE.; about 1 ch. E. of line a large draw draining from the N. enters the canyon; yellow pine becomes medium dense.
18.90	Top of a ledge 10 ft. high, bears S. 70° W. and N. 80° E.
21.80	Main draw, drains S. 60° E., 70 lks. to junction, thence S.; asc. over S. slope.
24.00	Small draw, drains S. 5° E. from N.; asc. along bottom of draw.
35.30	Spur ridge, 647 ft. above sec. cor., bears S. 70° W. and S. 70° E. 1½ chs. W. of line a branch projects N. 10° E.; desc. 75 ft. along E. slope of spurs to ¼ sec. cor.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for the ¼ sec. cor., with brass cap mkd.
	¼ S6 S5
	1933
 from which
	A yellow pine, 14 ins. diam., bears S. 79° E., 97 lks. dist., mkd. ¼S5BT.
	A yellow pine, 24 ins. diam., bears N. 33° W., 61 lks. dist., mkd. ¼S6BT.
40.30	Head of a branch canyon, drains E. from low saddle 1 ch. W.; asc. E. slope 43 ft.
43.70	Low spur divide, projects S. to junction from N. 20° E.; desc. along W. slope.
50.50	Bottom of a broad canyon, 52 ft. below spur, drains SW. about 5 chs., thence W. from head N. 20° E., about 5 chs. dist.; asc. over steep S. slope.
58.50	Spur, 200 ft. above canyon, projects W. from N. 80° E. for about 5 chs. thence from NE.; desc. over heavily timbered NW. slope.
67.20	Branch canyon, 150 ft. below spur, drains S. 70° W. from N. 80° E.; asc. steep SW. slope 331 ft.
71.60	Slope changes to S.; asc. 300 ft.
89.36	Intersect the N. bdy. of the township.
	Set an iron post, 3 ft. long, 2 ins. diam., 34 ins. in the ground, for the closing cor. of secs. 5 and 6, with brass cap mkd.

T19SR56E
S31

T19SR56E

S6 | S5

CC

1933