

E. ESTABLISHMENT OF $\frac{1}{4}$ SEC. CORS. ON THE NORTH BDY. OF T. 19 S., R. 56 E.

Chains

ESTABLISHMENT OF ONE-QUARTER SECTION CORNERS ON THE NORTH BOUNDARY OF T. 19 S., R. 56 E.

Establishment of $\frac{1}{4}$ sec. cor. on N. bdy. of sec. 1.

From the cor. of secs. 35 and 36, T. 18 S., R. 56 E., heretofore described.

N. $80^{\circ}56'$ E., 20.39 chs., along the N. bdy. of sec. 1.

At a point which is 40.00 chs. in departure East from the closing cor. of secs. 1 and 2, heretofore described.

Set an iron post, 3 ft. long, 1 in. diam., over a cross (X) on solid rock and surrounded by a mound of stone 8 ft. diam., at base to top of post, for the $\frac{1}{4}$ sec. cor. of sec. 1, with brass cap mkd.

$\frac{1}{4}$ S1

1934

from which

A yellow pine, 14 ins. diam., bears S. $42^{\circ}42'$ W., 111 lks. dist., mkd. $\frac{1}{4}$ S1BT.

A yellow pine, 12 ins. diam., bears S. $20^{\circ}\frac{1}{2}'$ E., 218 lks. dist., mkd. $\frac{1}{4}$ S1BT.

Cor. is set on a rocky W. slope about 25 lks. from the top of a spur.

No $\frac{1}{4}$ sec. cor. was established on the N. bdy. of sec. 2 for the reason that there are no public lands in this sec. to which the $\frac{1}{4}$ sec. cor. of sec. 2 would refer.

Establishment of $\frac{1}{4}$ sec. cor. on North bdy. of sec. 3.

From the restored cor. of secs. 33 and 34, T. 18 S., R. 56 E., heretofore described.

S. $84^{\circ}13'$ E., 16.725 chs. along the N. bdy. of sec. 3.

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground to bedrock, and in a large mound of stone to top of post, for witness $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$ S3 W

C

1933

from which

A cattail pine, 18 ins. diam., bears S. 50° E., 92 lks. dist., mkd. $\frac{1}{4}$ S3WCBT.

A cattail pine, 20 ins. diam., bears S. 30° W., 1.72 chs. dist., mkd. $\frac{1}{4}$ S3WCBT.

Note.— True point for cor. falls 20 lks. S. $84^{\circ}13'$ E., at the base of a large tree where it is impossible to set the cor; witness cor. is therefore set as described above.