

see pg 101 + 102 of inserted notes (see pg. 632) 461

METES AND BOUNDS SURVEY OF PRIVATE CLAIMS T. 19 S., R. 56 E.

Chains

projected S. from the accepted property cor. on the N. portion of the W. bdy. to an intersection with control brought S. and E. of the original cor. of secs. 2, 3, 34, and 35. The S. bdy. was surveyed E., cardinal course and record dist., the E. bdy. was projected N. from the SE. cor. of the claim to an intersection with the N. bdy. of the township.

Beginning at the NE. cor. of the claim.

Set an iron post, 3 ft., long, 1 in. diam., 12 ins. in the ground, and in a large mound of stone, for angle point 1/38, with brass cap mkd.

T18SR56E
S. 35

AP 1 S 1
TR 38

T19S R56E
1934

Thence

S. 80°56' W., along the N. bdy. of the tract, which is also the N. bdy. of the township.

4.97 The closing cor. of secs. 1 and 2, heretofore described.

20.34 The original 1/4 sec. cor. of secs. 2 and 35, which serves as angle point 2/38 and 1/40, heretofore described.

Thence

S. 0°16' E., bet. tracts 38 and 40; along an old blazed line.

19.83 Angle point 1/39 and 9/40, hereinafter described.

Thence

South, bet. tracts 38 and 39.

60.31 Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground, and in a large mound of stone, for angle points 3/38, 4/39, 1/44, and 2/46, with brass cap mkd.

T19SR56E
S11

TR 39 | TR 38
AP 4 | AP 3

AP 1 | AP 2
TR 44 | TR 46

1934

Thence

East, bet. tracts 38 and 46.

20.00 Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground, and in a mound of stone to top of post, for angle point 4/38, with brass cap mkd.