

464

see pg 104 & 105 inserted
 notes. (see pg. 635)

METES AND BOUNDS SURVEY OF PRIVATE CLAIMS T. 19 S., R. 56 E.

Chains

identical with adjoining bdrs. of tracts 38 and 39, previously determined. The remainder of the tract bdrs. are established either in harmony with the control furnished by the two original cors. on the N. bdy., or confined to the limits of the reestablished N. bdy. of the township at record courses and distances.

Beginning at the original $\frac{1}{4}$ sec. cor. of secs. 2 and 35, heretofore described.

Thence

S. $89^{\circ}25'$ W., along the N. bdy. of the township.

37.83

The original cor. of secs. 2, 3, 34, and 35, which is now mkd. by an iron post, 3 ft. long, 2 ins. diam., set 28 ins. in the ground, for the cor. of secs. 34 and 35, T. 18 S., R. 56 E., and angle point 2/40, with brass cap mkd.

T18SR56E

S34	S35
S2	

AP 2 TR 40
 T19SR56E
 1929

Thence

N. $84^{\circ}13'$ W., along the reestablished N. bdy. of the township.

20.10

A point which is 20.00 chs. in departure West from the original cor. of secs. 2, 3, 34, and 35.

Set an iron post, 3 ft. long, 1 in. diam., 4 ins. in the ground, to solid rock, and in a large mound of stone to top of post, for angle point 3/40, with brass cap mkd.

T18S

T19S	AP - 3
R56E	TR 40
S2	

1933

from which

A yellow pine, 16 ins. diam., bears S. 10° W., 72 lks. dist., mkd. BT, only.

Thence

South, bet. tract 40 and public land.

61.78

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, and deposit a limestone, 9x7x3 ins., mkd. with a cross (X) at base of post, for angle point 4/40, with brass cap mkd.

T19S	TR40
R56E	AP 4
S2	

TR 43

1933

from which