see gg 108 genserted nates (see 44 639)

METES AND BOUNDS SURVEY OF PRIVATE CLAIMS T. 19 S., R. 56 E.

Chains

Control for the location of this entry is taken from the original cor. of secs. 5, 6, 7, and 8, and the original \$\frac{1}{4}\$ sec. cor. of secs. 6 and 7. Where these points do not furnish sufficient control, the bdrs. are conformed to record courses and distances, with the exception of the W. bdy., which is conformed to the reestablished W. bdy. of the township bet. the intersections of the N. and S. bdrs.

Beginning at the NE. cor. of the claim, which is midpoint in distance bet. the original $\frac{1}{4}$ and sec. cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for angle point 1/42, with brass cap mkd.

T19SR56E S6 AP 1 TR 42

from which,

A mahogany, 6 ins. diam., bears S. 8°45' W., 47½ lks. dist., mkd. TR42AP1BT.

Thence

N. 89°02' W., on true line bet. the original $\frac{1}{4}$ sec. cor. and sec. cor., bet. tract 42 and public land.

The original $\frac{1}{4}$ sec. cor. of secs. 6 and 7, which is a limestone, 12x6x4 ins., broken in two and lying in a scattered mound of stone, poorly mkd. $\frac{1}{4}$ on one face.

At point for cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for angle point 2/42, with brass cap mkd.

T19SR56E S6 AP 2 TR 42

Note-. Destroy old BT. and remark old cor. stone AP and set alongside post.

Thence assumed to real out 18 then a

West, bet. tract 42 and public land.

33.13 | Intersect the W. bdy. of the township.

At point of intersection,

Set an iron post, 3 ft. long, 1 in. diam., 24 ins. in the ground, and in a mound of stone to top of post, for angle point 3/42, with brass cap mkd.

T. S. GOVERNMENT PRINTING OFFICE: 10ML 6-8155