

625
DEPENDENT RESURVEY OF EAST BDY. OF T. 19 S., R. 56 E.

Chains

COMPLETION OF THE DEPENDENT RESURVEY OF THE E. BDY. OF
T. 19 S., R. 56 E.

REESTABLISHMENT OF SURVEYS EXECUTED BY THEODORE BINGE,
U. S. DEPUTY SURVEYOR, IN 1881.

Commence the resurvey at the cor. of secs. 19, 24, 25,
and 30, Tps. 19 S., Rs. 56 and 57 E., which is an iron
post, 2 ins. diam., firmly set, mkd. and witnessed, as
described in the official record.

N. 1°13' E., on true line bet. secs. 19 and 24.

Over rough mountainous land, through dense timber,
medium dense undergrowth; desc. NE. slope.

1.80 Slope changes to SE.

8.10 Slope changes to NE.

12.80 Small draw, drains E. about 5.00 chs. to main draw,
thence SE.

18.65 Draw, 215 ft. below sec. cor., drains SE.; asc. steep
slope 685 ft. to 39.93 ch. point. (Fletcher Canyon)

25.10 Top of a cliff, 300 ft. high.

39.93 Proportionate point for $\frac{1}{4}$ sec. cor.,

Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in
the ground, and in a mound of stone to top, for $\frac{1}{4}$ sec.
cor., with brass cap mkd.

$\frac{1}{4}$

S24 | S19

1929

from which

A yellow pine, 10 ins. diam., bears S. 77° E.,
42 lks. dist., mkd. $\frac{1}{4}$ S19BT.

A fir, 10 ins. diam., bears N. 44-3/4° W., 44
lks. dist., mkd. $\frac{1}{4}$ S24BT.

51.00 Rocky spur, projects SE.; asc. along an E. slope.

56.00 Small draw, drains SE.; asc. E. to SE. slope.

65.30 Spur, 544 ft. above $\frac{1}{4}$ sec. cor., projects S. 20° E.;
asc. along E. slope.

67.70 Small draw, 17 ft. below spur, drains S. 20° E.; asc.
along SE. slope 340 ft. to 79.865 ch. point.

70.10 Top of small rocky spur, projects SW., 3.00 chs., to end.