

METES AND BOUNDS SURVEY OF PRIVATE CLAIMS IN T. 19 S., R. 56 E.

Chains

Thence,

From the true point for Angle Point 5/37,

N. $86^{\circ}03'$ E., along the south boundary, bet. Tract No. 37 and public land in Sec. 13

19.87

Point for Angle Point 6/37 falls on precipitous slope where it is impracticable to establish corner monument. Therefore, at an accessible position on safe ground, N. $7^{\circ}26'$ W., 1.37 chs. distant, Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for witness angle point 6/37, with brass cap mkd.

T19S R56E
WC
AP 6
TR 37
S 13
1937

from which

A cattail pine, 36 ins. diam., bears S. $35\frac{1}{2}^{\circ}$ E., 71 lks. dist. mkd. WC AP6 TR37 BT.

Thence,

From true point for Angle Point 6/37,

S. $1^{\circ}10'$ W., along west boundary, bet. Tract No. 37 and public land in Sec. 13,

19.83

Point for Angle Point 7/37 falls in slide rock area where it is unsafe to establish a corner monument. Therefore, at a point N. $9^{\circ}09'$ W., 1.25 chs. distant, at base of cliff and in a large crevice,

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in a mound of stone, for witness angle point 7/37, with brass cap mkd.

T19S R56E
S 13 AP 7
WC TR 37
1937

from which

A cattail pine, 30 ins. diam., bears S. $64\frac{1}{2}^{\circ}$ E., 28 lks. dist. mkd. WC AP7 TR37 BT.

Thence,

From true point for angle point 7/37,

N. $86^{\circ}27'$ E., along the south boundary, bet. Tract No. 37 and public land in Sec. 13,

19.84

Intersect the E. bdy. of the Tp., N. $1^{\circ}13'$ E., 19.96 chs. dist. from the cor. of secs. 13, 18, 19 and 24, heretofore described. The point of intersection is identical with the point for the S. $1/16$ th sec. cor. of secs. 13 and 18 and for angle point 8/37.

Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground to solid rock and in a large supporting mound of stone to top of post, for the S. $1/16$ th sec. cor. of secs. 13 and 18, and angle point 8/37, with