

DEPENDENT RESURVEY OF SUBDIVISION OF T.20 N., R.25 E.

Chains

REESTABLISHMENT OF SURVEYS EXECUTED BY
BARKER AND EATON, U.S. DEPUTY SURVEYORS
IN 1878.


From the cor. of secs. 1, 2, 35, and 36 on the S. bdy. of the Tp. heretofore described.

N.0°11'W., bet. secs. 35 and 36.

Along rocky E. slope over mountainous land through short shadscale, sagebrush and yellow top undergrowth.

- 8.60 Spur, 45 ft. below sec. cor., descends to the NE. and comes from ridge about 3 chs. W.; descend over N. slope.
- 12.95 Head of draw, 50 ft. below spur, drains NW.
- 20.40 Same draw, drains NE.
- 25.60 Same draw, drains NW.; ascend over SW. slope.
- 28.65 Top of ascent, 45 ft. above draw, bears NW. and SE.; gradually descend over N. slope.
- 40.42 Proportionate point.


Set an iron post, 3 ft. long, 1 in. in dia., 6 ins. in the ground on solid rock and supported by a large mound of stone 8 ft. base to top for $\frac{1}{4}$ sec. cor., with brass cap marked



Cor. stands on E. side of bottom of broad, shallow, sandy draw draining N., 60 ft. below top of ascent.

- 41.35 Broad, shallow draw, drains N.30°E.; thence along W. side of bottom of draw.
- 55.00 Leave draw at foot of spur, bears NE. and SW.; ascend 40 ft. to
- 66.75 Spur, projects NE.; gradually descend over N. slope.
- 73.70 Draw, 55 ft. below spur, drains NE.; ascend.
- 80.84 Proportionate point.

Set an iron post, 3 ft. long, 2 ins. in dia., 26 ins. in the ground for cor. of secs. 25, 26, 35, and 36, with brass cap marked



raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

Cor. stands on a low spur projecting NE., 20 ft. above draw.