


INDEPENDENT RESURVEY OF THE SUBDIVISION OF T 41 N, R 21 E.

Chains


Establishment of the corner of sections 25 and 36 on the east boundary of the township.

The original corner of sections 25, 30, 31, and 36, T 41 N, Rs 21 and 22 E, remonumented in 1927 by Emil Voigt, U. S. Cadastral Engineer, as the corner of sections 25 and 36, T 41 N, R 21 E, and which is now marked by an iron post, 2 ins. in diameter, firmly set, properly marked and witnessed as described in the official record. This corner now becomes an angle point and its brass cap is remarked as follows:



At a point 0.62 chains N 5°59' E of the above described angle point, on line on the east boundary and at a point 80.00 chains in northing from the standard corner of T 41 N, Rs 21 and 22 E, on the 8th Standard Parallel North, heretofore described:

Over a cross (X) cut into solid bedrock: Set an iron post, 3 ft. long and 2 ins. in diameter, 4 ins. in the ground to solid rock and in a mound of stone, for the corner of sections 25 and 36, T 41 N, R 21 E, with brass cap marked:



No suitable accessories available.

Beginning at the corner of sections 25 and 36 on the east boundary of the township, heretofore described, thence:

West, on a random sectional correction line between sections 25 and 36.

40.05 Set a temporary 1/4 section corner.

80.10 Computed distance: Set a temporary point. Thence

South, on a random sectional guide meridian between sections 35 and 36.

40.00 Set a temporary 1/4 section corner.

81.49 Intersect the 8th Standard Parallel North at a point 02 lks east of the standard corner of sections 35 and 36, heretofore described, thence, from that corner:

North, on true line between sections 35 and 36.

Over rolling hills, through a scant undergrowth of sage and shadscale, descend 35 ft. along a NW slope.