

INDEPENDENT RESURVEY OF SUBDIVISION OF T. 41 N., R. 21 E.

Chains

Continue gradual descent along NE. slope.

54.30 Draw, drains E. from the W.; ascend rocky SE. slope.

58.60 Spur, projects S. 50° E.

65.10 Draw, drains S. 20° E.; ascend S. slope.

75.28 On rocky S. slope, 130 ft. above the draw at the 54.30 chs. point.

Intersect the N. bdy. of the township at a point, S. 88°21' W., 12.39 chs. dist. from the $\frac{1}{4}$ sec. cor. of sec. 33, T. 42 N., R. 21 E., heretofore described.

At point of intersection.

Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, for closing cor. of secs. 3 and 4, T. 41 N., R. 21 E., with brass cap marked

T42N R21E

S33

S4

S3

T41N R21E

C C

1932

Raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.

Land, hilly and mountainous with a general southeasterly exposure and drainage.

Soil, rocky and gravelly clay and sand loams; 3rd rate.

Undergrowth, sage and buck brush.

No timber.

Fair grazing land.

From the cor. of secs. 27, 28, 33, and 34, heretofore described.

West, on random sectional correction line, bet. secs. 28 and 33.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

80.00 Set temp. cor. of secs. 28, 29, 32, and 33.

S0°02'E on random line, bet. secs. 32 and 33.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

86.01 Intersect the 8th Standard Parallel North at the standard cor. of secs. 32 and 33, heretofore described.

Thence

N. 0°02' W., on true line, bet. secs. 32 and 33.