

INDEPENDENT RESURVEY OF THE SUBDIVISION OF T. 41 N., R. 21 E.

Chains

West, on sectional correction line, bet. secs. 29 and 32.
Over rolling mountainous land through medium dense undergrowth; ascend 130 ft. over rocky E. slope.

11.30 Top of ridge, bears N. 20° W. and S. 20° E.; descend 340 ft. over rocky SW. slope, to the $\frac{1}{4}$ sec. cor.

40.02 On W. slope.

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked

$\frac{1}{4}$ S29
S32

1932

Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

Continue descent of 240 ft. over W. slope, to sec. cor.

61.50 Draw, drains SW.

80.04 The cor. of secs. 29, 30, 31, and 32.

Land, mountainous, with rolling slopes and hills, with a general westerly exposure and drainage.

Soil, shallow sandy loam underlayed with gravel and rock; 3rd rate.

Undergrowth, sage and buck brush.

No timber.

Fair grazing land.

West, on a true sectional correction line, bet. secs. 30 and 31.

Over rolling mountainous land through dense undergrowth; descend 155 ft. over a gradual W. slope to the $\frac{1}{4}$ sec. cor.

40.00 On table land.

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked

$\frac{1}{4}$ S30
S31

1932

Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

Thence across flat sandy bottom lands.

43.20 Old road, bears N. 40° W. and S. 30° E.

55.60 Main wash, drains N.

69.92 Intersect the W. bdy. of the township, N. 0°42' E., 9.40 chs. dist. from the cor. of secs. 25 and 36, T. 41 N., R. 20 E., heretofore described.

At point of intersection: