

178

## INDEPENDENT RESURVEY OF THE SUBDIVISION OF T. 41 N., R. 21 E.

Chains

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap marked

$$\frac{1}{4} \frac{S17}{S20}$$

1932

Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.  
Descend 325 ft. over rocky NW. slope to draw.

43.50 Spur, projects N.

65.60 Draw, drains N. 50° W. and heads 3.00 chs. SE.; ascend 180 ft. along N. slope.

80.16 The cor. of secs. 17, 18, 19, and 20.

Land, rocky and mountainous, with a general northwesterly exposure and drainage.

Soil, rocky; 3rd rate.

Undergrowth, sage and buck brush.

No timber.

Fair grazing land.

---

West, on true line, bet. secs. 18 and 19.

Over broken mountainous land through dense undergrowth; descend 230 ft. over NW. slope.

18.10 Spur, projects N. 20° W.; continue descent over SW. slope.

40.00 On W. slope; mark a cross (X) on the bedrock, over which:

Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground to bedrock and in a mound of stone to top, for  $\frac{1}{4}$  sec. cor., with brass cap marked

$$\frac{1}{4} \frac{S18}{S19}$$

1932

Descend 140 ft. over general W. slope to closing cor.

45.00 Spur, projects NW 20° W.

59.10 Top of rough broken outcropping, bears N. and S.

67.11 Intersect the W. bdy. of the township, N. 0°47' E., 9.83 chs. dist. from the cor. of secs. 13 and 24, T. 41 N., R. 20 E., heretofore described.

At point of intersection.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for closing cor. of secs. 18 and 19, T. 41 N., R. 21 E., with brass cap marked