


INDEPENDENT RESURVEY OF THE SUBDIVISION OF T. 41 N., R. 21 E.

Chains

32.00 Spur, projects N.; descend gradual W. slope.

40.00 On gradual W. slope.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for 1/4 sec. cor., with brass cap marked



1932


Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

Continue descent over W. slope 60 ft. to closing cor.

65.94 Intersect the W. bdy. of the township, N. 0°46' E., 9.94 chs. dist. from the cor. of secs. 12 and 13, T. 41 N., R. 20 E., heretofore described.

At point of intersection:

Set an iron post, 3 ft. long, 2 ins. diam., 15 ins. in the ground to solid rock and in a mound of stone to top, for closing cor. of secs. 7 and 18, T. 41 N., R. 21 E., with brass cap marked



1932

Deposit a stone, 4 x 3 x 2 ins., at base of post, marked with a cross (X).

Land, rolling, with a general westerly exposure and drainage.

Soil, shallow sandy loam 3 ins. deep underlayed with rock and gravel; 3rd rate.

Undergrowth, sagebrush, yellow top, buck brush and bunch grass.

No timber.

Poor to fair grazing land.

From the cor. of secs. 7, 8, 17, and 18.

N. 0°03' W., bet. secs. 7 and 8.

Over rolling bench land through dense undergrowth; descend 80 ft. over gentle W. slope to the 1/4 sec. cor.

40.00 On gentle W. slope.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for 1/4 sec. cor., with brass cap marked