

INDEPENDENT RESURVEY OF THE SUBDIVISION OF T. 41 N., R. 21 E.

Chains

1/4 sec. cor., with brass cap marked

85
1/4 ---
88

1932

Continue descent of 220 ft. over W. slope to sec. cor.

80.12 The cor. of secs. 5, 6, 7, and 8.

Land, broken bench land with a general southwesterly exposure and drainage.

Soil, gravelly and rocky; 3rd rate.

Undergrowth, sagebrush.

No timber.

Fair grazing land.

West, on true line, bet. secs. 6 and 7.

Over nearly level bench land through dense undergrowth; descend 130 ft. over gradual NW. slope.

19.40 Low top of spur, projects N. and bears S.; descend 50 ft. to the 1/4 sec. cor.

40.00 On gradual W. slope.

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for 1/4 sec. cor., with brass cap marked

S6
1/4 ---
S7

1932

Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

Descend 50 ft. over gradual W. slope to closing cor.

64.88 Intersect the W. bdy. of the township, N. 0°45' E., 10.05 chs. dist. from the cor. of secs. 1 and 12, T. 41 N., R. 20 E., heretofore described

At point of intersection:

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for closing cor. of secs. 6 and 7, T. 41 N., R. 21 E., with brass cap marked

T41N
R20E R21E
S1 | S6 --- C
 | S7 --- C

1932

Raise a mound of stone, 3 ft. base, 2 ft. high, E. of cor.