

ESTABLISHMENT OF ONE-QUARTER SECTION CORNERS BETWEEN CLOSING CORNERS ON NORTH BOUNDARY FOR T. 41 N., R. 21 E.

Chains 94.10 The cor. of Ts. 41 and 42 N., Rs. 20 and 21 E., heretofore described.

ESTABLISHMENT OF ONE-QUARTER SECTION CORNERS BETWEEN CLOSING CORNERS ON WEST BOUNDARY FOR T. 41 N., R. 21 E.


From the standard cor. of T. 41 N., Rs. 20 and 21 E., heretofore described.

N. 0°35' E., along the E. bdy. of sec. 36, T. 41 N., R. 20 E.

8.76 Point which is a southing of 80.00 chs. from the closing cor. of secs. 30 and 31, T. 41 N., R. 21 E., and true point for the cor. of Lots Nos. 8 and 15, sec. 31.

True point for cor. falls in bottom of dry channel where it is impracticable to set a permanent cor., therefore at;

9.36 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground to solid rock and in a mound of stone to top, for witness cor. to the cor. of Lots Nos. 8 and 15, T. 41 N., R. 21 E., with brass cap marked



1932

Deposit a stone, 6 x 5 x 4 ins., at base of post, marked with a cross (X).

39.38 The 1/4 sec. cor. sec. 36, T. 41 N., R. 20 E., heretofore described.

Thence, N. 0°27' E., with continuous measurement.

48.76 Point which is a southing of 40.00 chs. from the closing cor. of secs. 30 and 31, T. 41 N., R. 21 E.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for 1/4 sec. cor. sec. 31, T. 41 N., R. 21 E., with brass cap marked



1932

Raise a mound of stone, 3 ft. base, 2 ft. high, E. of cor.

79.36 The cor. of secs. 25 and 36, T. 41 N., R. 20 E., heretofore described.

N. 0°42' E., along the E. bdy. sec. 25, T. 41 N., R. 20 E.

9.40 The closing cor. of secs. 30 and 31, T. 41 N., R. 21 E., heretofore described.

39.96 The 1/4 sec. cor. for sec. 25, T. 41 N., R. 20 E., heretofore described.