

West Boundary of T. 27 N., R. 40 E.

Chains Land, mountainous. Soil, gravelly loam, 3rd rate.
 Timber, scattering juniper. Undergrowth, sage, shadscale.
 General drainage, SE. Grazing, poor.

Establishment of Corners on S. Boundary of T. 27 N., R. 40 E.

All corners on S. boundary of this township were set at regular intervals of 40.00 and 80.00 chs. West of the cor. of T. 27 N., Rs. 40 and 41 E.
 Corners on this boundary referring to T. 26 N., R. 40 E. were set by me in survey of T. 26 N., R. 40 E., under Group No. 113 during 1928 and descriptions of same are omitted from these notes

At a point 18.68 chs. East of the $\frac{1}{4}$ sec. cor. of sec. 1
 Set an iron post, 3 ft. long, 1 in. dia., 27 ins. in the ground, for the $\frac{1}{4}$ sec. cor. of sec. 36 only, with brass cap mkd
 $\frac{1}{4}$ S36
 1929

Raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, N. of cor.

At a point 18.68 chs. East of the cor. of secs. 1 and 2

Set an iron post, 3 ft. long, 2 ins. dia., 27 ins. in the ground, for the cor. of secs. 35 and 36, with brass cap mkd
 T27N R40E
 $\frac{S35}{S36}$
 S1
 T26N
 1929

Raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, N. of cor.

At a point 18.68 chs. East of the $\frac{1}{4}$ sec. cor. of sec. 2

Set an iron post, 3 ft. long, 1 in. dia., 20 ins. in the ground, in a mound of stone, for the $\frac{1}{4}$ sec. cor. of sec. 35 only, with brass cap mkd
 $\frac{1}{4}$ S35
 1929

At base of post deposit a mkd(X) quartzite stone, 4x6x6

At a point 18.68 chs. East of the cor. of secs. 2 and 3