

Subdivisions T. 27 N., R. 40 E.

Chains	N. 0° 03' W., between secs. 4 and 5
	Over rolling bench land
	Asc. along E. slope 70 ft. to 44.50
12.10	Road, bears N. 40° W. and S. 40° E. about 8 chs., thence NE.
40.00	Set an iron post, 3 ft. long, 1 in. dia., 27 ins. in the ground, for the $\frac{1}{4}$ sec. cor., with brass cap mkd
	$\frac{1}{4}$
	S5 S4
	1929
	Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
40.50	Road, bears N. 50° W. and S. 50° E.
44.50	Main wash, 20 lks. wide, 8 ft. deep, drains S. 75° E.
	Thence over bottom land
51.10	Wash, 5 lks. wide, 3 ft. deep, drains N. 75° E.
	Asc. S. slope 30 ft. to
57.00	Top of knoll
	Desc. N. slope 20 ft. to
58.10	Thence over bottom land
69.00	Asc. S. slope 35 ft. to
72.10	Thence over level bench land
75.47	Intersect N. boundary of the township, 7.28 chs. W. of the cor. of secs. 4, 5, 32 and 33, which is a 2 in. iron post, firmly set in the ground, and marked and witnessed as described in the official records of the survey of T. 28 N., R. 40 E., I remark same to read
	T28NR40E
	S32 S33
	S4
	T27N
	1929
	Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.
	At point of intersection