

Subdivisions T. 27 N., R. 40 E.

Chains
 7.80 Main wash, 10 lks. wide, 2 ft. deep, drains S. 80° E.
 Asc. SW. slope 30 ft. to
 9.90 Desc. NE. slope 30 ft. to
 15.75 Main wash, 20 lks. wide, 2 ft. deep, drains E.
 Asc. SW. slope 225 ft. to 52.50
 35.15 Main wash, 10 lks. wide, 2 ft. deep, drains S. 20° E.
 40.00 Set an iron post, 3 ft. long, 1 in. dia., 27 ins. in the
 ground, for the $\frac{1}{4}$ sec. cor., with brass cap mkd

$\frac{1}{4}$
 S6 | S5

1929

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
 52.50 Thence across nearly level bench land
 General ascent
 75.75 Intersect N. boundary of township, 6.96 chs. W. of the
 cor. of secs. 5, 6, 31 and 32, which is a 2 in. iron
 post, firmly set in the ground, and marked and
 witnessed as described in the official records of the
 survey of T. 28 N., R. 40 E., I remark same to read:

T28NR40E

S31 | S32

S5

T27N

1929

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.

At point of intersection

Set an iron post, 3 ft. long, 2 ins. dia., 27 ins. in
 closing
 the ground, for the cor. of secs. 5 and 6, with brass

cap mkd

T28N

S31

S6 | S5

QC

T27NR40E

1929

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, S. of cor.