

DEPENDENT RESURVEY EAST BOUNDARY OF T. 23 N., R. 34 E.

Chains

458.09

Fall 2.16 chs. N. of temp. cor. of Tps. 23 and 24 N., Rs. 34 and 35 E.

True lines.

At proportionate point, set an iron post, 3 ft. long, 3 ins. diam., 8 ins. in the ground to solid rock, in a large mound of stone, for the reestablished cor. of Tps. 22 and 23 N., Rs. 34 and 35 E., with brass cap mkd.

T23N	
R34E	R35E
S36	S31
S1	S6

T22N
1931

At base of post deposit a mkd.(X) shale stone, 8x7x3 ins.

The cor. of Tps. 24 and 25 N., Rs. 34 and 35 E., which is a granite stone, 18x12x12 ins., above ground, firmly set, marked and witnessed as described in the official record, bears N. 0° 10' E., 959.07 chs. dist.

The cor. of secs. 4, 5, 32, and 33, Tps. 22 and 23 N., R. 35 E., which is a granite stone, 16x12x10 ins., above ground, firmly set, marked and witnessed as described in the official record, bears N. 89° 20' E., 158.40 chs. dist.

The cor. of secs. 7, 12, 13, and 18, Tps. 22 N., Rs. 34 and 35 E., which is a trap stone, 16x12x10 ins., above ground, firmly set, marked and witnessed as described in the official record, bears S. 1° 50' W., 159.92 chs. dist.

From the reestablished cor. of Tps. 22 and 23 N., Rs. 34 and 35 E.

N. 1° 47' E., on dependent resurvey bet. secs. 31 and 36.

Over rough mountainous land, through scattering timber and undergrowth.

Asc. rocky precipitous SW. slope over rock slides and ledges 1205 ft. to

36.75

Rocky ridge, bears E. and W. about 10 chs., thence NW; head of two ravines in saddle, draining N. and S., about 8 chs. W. of line.

Desc. steep, rocky N. to NW. slope 605 ft. to 62.00 chs.

39.98

Proportionate point for $\frac{1}{4}$ sec. cor., set an iron post, 3 ft. long, 1 in. diam., 8 ins. in the ground to solid rock, in a mound of stone, for the $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$	
S36	S31

1931

At base of post deposit a mkd.(X) granite stone, 8x6x4 ins. No suitable trees available within limits.

62.00

Rocky ravine, drains E.