

DEPENDENT RESURVEY WEST BOUNDARY T. 23 N., R. 34 E.

- Chains The cor. of Tps. 21 and 22 N., R. 33 E., which is an iron post, 3 ins. diam., 9 ins. above ground, firmly set, marked and witnessed as described in the official record, bears S. $0^{\circ} 30'$ E., 482.18 chs. dist.
- The cor. of Tps. 22 and 23 N., Rs. 32 and 33 E., where I find evidences of four pits, one in each township, NE, SE, SW, and NW, and decayed fragments of a stake in a mound of earth, bears N. $89^{\circ} 58'$ W., 478.65 chs. dist. In center of mound I set a granite stone, 22x16x8 ins. 15 ins. in the ground, for the cor. of Tps. 22 and 23 N., Rs. 32 and 33 E., mkd.
- 6 grooves on N, E, S, and W edges
- raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, S. of cor.
- From the cor. of Tps. 22 and 23 N., R. 33 E.
- N. $0^{\circ} 06'$ E., on dependent resurvey along the E. boundary of sec. 36, T. 23 N., R. 33 E.
- Over rough mountainous land, through scattering undergrowth.
- Desc. steep rocky NW. slope 115 ft. to 3.90 chs.
- 2.10 Point for closing cor. of Tps. 22 and 23 N.; R. 34 E., hereinafter described.
- 3.90 Main canyon, steep and rocky, drains N. 60° W.
- Asc. steep rocky SW. slope 60 ft. to
- 7.90 Spur, projects N. 80° W.
- Desc. rocky NW. slope 60 ft. to
- 9.75 Steep rocky ravine, drains N. 85° W., heads about 8 chs. E.
- Asc. rocky SW. slope 45 ft. to
- 11.90 Rocky spur, projects S. 45° W.
- Desc. steep rocky NW. slope 35 ft. to
- 14.50 Rocky ravine, drains S. 50° W.
- Asc. steep rocky SE. slope 205 ft. to
- 23.70 Spur ridge, projects W. from S. 70° E.
- Desc. steep rocky N. slope 405 ft. to 33.45 chs.
- 29.35 Portal of abandoned tunnel, bears W. 50 lks. dist.
- 33.45 Steep rocky main canyon, drains W. about 1 ch., thence N. 70° W.
- Asc. precipitous rocky SW. slope over numerous ledges and slides 545 ft. to 58.25 chs.
- 35.18 Set an iron post, 3 ft. long, 1 in. diam., on rocky shelf over a chiseled X, and in a mound of stone, for witness $\frac{1}{4}$ sec. cor., with brass cap mkd.