


SURVEY OF SOUTH BOUNDARY OF T. 23 N., R. 34 E.

Chains

3 ins. diam., 22 ins. in the ground to bedrock, with a granite stone, 9x5x4 ins., mkd. X, deposited at the base, and in a mound of stone, for the closing cor. of Tps. 22 and 23 N., R. 34 E., with brass cap mkd.



Land, rough mountainous. Soil, rocky, 4th rate.
 Timber, scattering juniper, pinon.
 Undergrowth, sagebrush.
 General drainage, E. 13 chs. to SE., W. 67 chs. to NW.
 Grazing, poor.

SURVEY OF NORTH BOUNDARY OF T. 23 N., R. 34 E.

From the cor. of Tps. 23 and 24 N., Rs. 34 and 35 E.

West, on a random line setting temp. $\frac{1}{4}$ sec. and sec. cors. at regular intervals of 40.00 and 80.00 chs., and at

500.06 Fall 44 lks. S. of the cor. of Tps. 23 and 24 N., Rs. 33 and 34 E.

From the cor. of Tps. 23 and 24 N., Rs. 34 and 35 E.

N. $89^{\circ} 57'$ W., along S. bdy. of sec. 36, T. 24 N., R. 34 E.

Over rough mountainous land, through scattering timber and medium undergrowth.

Asc. rocky NE. slope 55 ft. to

13.25 Rocky spur, projects N. 35° W.

Desc. rocky SW. slope 145 ft. to

17.90 Bottom of a fork of Copper Kettle Canyon, drains N. 25° W.

Asc. precipitous rocky NE. slope 170 ft. to

21.80 Top of sharp rim rock, bears N. 15° W. and S. 15° E.

Desc. rocky W. slope 65 ft. to

23.00 Head of ravine, drains N.

Desc. along rocky N. slope 20 ft. to

36.10 Head of ravine, drains N. 15° W.

Asc. rocky NE. slope 30 ft. to 43.60 chs.

40.00 Set an iron post, 3 ft. long, 1 in. diam., on solid rock outcropping, over a chiseled X, and in a mound of stone, for the $\frac{1}{4}$ sec. cor. of sec. 36, with brass cap mkd.