

SUBDIVISION OF T. 23 N., R. 34 E.

Chains

79.99 Intersect N. bdy. of Tp., N. 89° 57' W., 14.60 chs. from the cor. of secs. 32 and 33, and at point of intersection; set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground to bedrock, with a granite stone, 6x4x3 ins., mkd. X, deposited at the base, and in a mound of stone, for the closing cor. of secs. 4 and 5, with brass cap mkd.

T24N

S32

S5 S4

CC

T23NR34E

1932

Land, rough mountainous. Soil, rocky with some gravel, 3rd and 4th rate. Timber, none. Undergrowth, sagebrush, greasewood, shadscale. General drainage, W. Grazing, poor.

From the cor. of secs. 5, 6, 31, and 32, on S. bdy. of Tp. N. 0° 03' W., bet. secs. 31 and 32.

Over rough mountainous land, through scattering timber and undergrowth.

Asc. steep rocky SW. slope 80 ft. to

2.30 Spur, projects S. 70° E. Asc. steep rocky SE. slope 535 ft. to 22.40 chs.

8.85 Head of ravine, drains S. 60° E.

22.40 Ridge, bears E. and W. about 5 chs., thence SW.

Desc. along precipitous rocky NW. slope over nearly impassable ledges and cliffs 310 ft. to 39.85 chs.

30.40 Solid rock point of spur, projects W.

39.85 Rocky ravine, drains N. 70° W., heads about 2 chs. SE.

Asc. steep rocky SW. slope 30 ft. to 41.00 chs.

40.00 Set an iron post, 3 ft. long, 1 in. diam., on solid rock outcropping, over a chiseled X, and in a mound of stone, for the  $\frac{1}{4}$  sec. cor., with brass cap mkd.

S31 S32

1931

41.00 Desc. steep rocky NW. slope 75 ft. to

45.80 Desc. rocky broken NW. slope 360 ft. to 72.20 chs.

52.35 Rocky ravine, drains N. 45° W., heads about 12 chs. SE.

64.60 Rocky ravine, drains N. 40° W., heads about 9 chs. SE.

72.20 Rocky canyon (heavy willow thicket), drains W.