

SUBDIVISION OF T. 23 N., R. 34 E.

Chains Desc. steep rocky SW. slope 105 ft. to
 4.80 Rocky ravine, drains S.
 Asc. steep rocky SE. slope 625 ft. to
 28.00 Sharp rocky ridge, bears NE. and SW.
 Desc. precipitous rocky NW. slope 420 ft. to 38.50 chs.
 38.50 Set an iron post, 3 ft. long, 1 in. diam., 8 ins. in
 the ground to bedrock, with a granite stone, 8x4x2 ins.,
 mkd. X, deposited at the base, and in a mound of stone,
 for the witness $\frac{1}{4}$ sec. cor., with brass cap mkd.
 $\frac{1}{4}$ S30 - WC
 S31
 1931
 40.00 Point for $\frac{1}{4}$ sec. cor. falls on NW. sloping face of
 rock ledge.
 Desc. precipitous rocky general NW. slope over nearly
 impassable cliffs and ledges 1160 ft. to closing cor.
 86.18 Intersect W. bdy. of Tp., N. 0° 06' E., 1.66 chs. from
 the cor. of secs. 25 and 26, and at point of
 intersection; set an iron post, 3 ft. long, 2 ins. diam.,
 6 ins. in the ground, to bedrock, with a granite stone,
 8x5x5 ins., mkd. X, deposited at the base, and in a
 mound of stone, for the closing cor. of secs. 30 and
 31, with brass cap mkd.
 T23N
 R33E | R34E
 S25 | S30 CC
 | S31
 1931
 Land, rough mountainous. Soil, rocky, 4th rate.
 Timber, juniper, pinon.
 Undergrowth, sagebrush, shadscale.
 General drainage, E. 28 chs. to SW., W. 52 chs. to NW.
 Grazing, poor.
 From the cor. of secs. 29, 30, 31, and 32.
 N. 0° 03' W., bet. secs. 29 and 30.
 Over rough mountainous land, through scattering timber
 and undergrowth.
 Asc. steep rocky SW. slope 240 ft. to
 11.00 High rocky ridge, bears E. and S. 70° W.; saddle is about
 7 chs. W. of line, with two ravines, draining N. and S.
 Desc. steep rocky NW. slope 165 ft. to
 19.10 Head of ravine, drains N. 60° W.
 Desc. along rocky W. slope 50 ft. to 28.25 chs.
 20.80 Rocky spur, projects N. 75° W.
 22.80 Head of ravine, drains N. 55° W.