

SUBDIVISION OF T. 23 N., R. 34 E.

Chains	
80.00	The cor. of secs. 19, 20, 29, and 30. Land, rough mountainous. Soil, rocky, 4th rate. Timber, juniper, pinon. Undergrowth, sagebrush. General drainage, N. Grazing, poor.
	West, bet. secs. 19 and 30. Over rough mountainous land, through scattering timber and undergrowth. Asc. precipitous rocky NE. slope 300 ft. to 6.05 chs.
3.39	Intersect line 2-3 M. S. No. 3825 New York Lode at a point from which cor. No. 3 bears North 2.21 chs. dist.
3.70	Base of 100 ft. cliff.
4.85	Top of cliff, bears NW. and SE.
6.05	Sharp jagged ridge, bears S. and NW. Desc. steep rocky SW. slope 570 ft. to
22.15	Steep rocky ravine, drains N. 40° W. Asc. rocky NE. slope 25 ft. to
27.45	Desc. general rocky NW. to N. slope 175 ft. to
39.90	Rocky spur, projects N. 55° W. Desc. general rocky SW. slope 270 ft. to 53.05 chs.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 10 ins. in the ground to bedrock, with a granite stone, 6x4x2 ins., mkd. X, deposited at the base, and in a mound of stone, for the 1/4 sec. cor., with brass cap mkd.
	S19 1/4 S30 1931
53.05	Rocky spur, projects N. 65° W. Desc. steep rocky general NW. slope 380 ft. to 60.05 chs.
56.50	Old abandoned mine shaft, 50 ft. deep, bears S. 30 lks. dist.
60.05	Desc. rocky broken SW. slope 285 ft. to
78.70	Base of mountains, bears NW. and SE.; thence over rolling mountainous land; desc. general W. slope 130 ft. to
86.09	Intersect W. bdy. of Tp., N. 0°06' E., 1.10 chs. from the cor. of secs. 24 and 25, and at point of intersec- tion set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground to bedrock, with a granite stone, 8x5x4 ins., mkd. X, deposited at the base, and in a mound of stone for the closing cor. of secs. 19 and 30, with brass cap mkd.
	T23N R33E R34E S19 S24 CC S30 1931