

SUBDIVISION OF T. 23 N., R. 34 E.

Chains

63.00 Rocky spur, projects N. about 3.50 chs., thence N. 45° W.  
Desc. rocky NW. slope 135 ft. to

67.65 Rocky ravine, drains N. 30° W., heads about 6.50 chs. S.  
Asc. rocky NE. slope 65 ft. to

71.40 Rocky spur, projects N. 15° W.  
General ascent along steep rocky N. slope over numerous ledges 10 ft. to 81.90 chs.

72.45 Ravine, drains N. 55° W., heads about 4 chs. S.

81.90 Rocky spur, projects N. 40° W.  
Desc. rocky SW. slope 75 ft. to

85.81 Intersect W. bdy. of Tp., N. 0° 06' E., 1.02 chs. from the cor. of secs. 13 and 24, and at point of intersection; set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground to bedrock, with a granite stone, 5x4x3 ins., mkd. X, deposited at the base, and in a mound of stone, for the closing cor. of secs. 18 and 19, with brass cap mkd.

T23N	
R33E	R34E
	S18
S13	S19

1932

Land, rough mountainous. Soil, rocky, 4th rate. Timber, scrub juniper, pinon. Undergrowth, sagebrush, shadscale, rabbit brush, squaw brush. General drainage, NW. Grazing, poor.

From the cor. of secs. 17, 18, 19, and 20.  
N. 0° 03' W., bet. secs. 17 and 18.  
Over rough mountainous land, through scattering timber and undergrowth.

Desc. along rocky NE. slope 25 ft. to

1.85 Rocky ravine, drains SE., heads about 1 ch. NW.  
Asc. rocky SW. slope 50 ft. to

5.30 Ridge, bears E. and SW., saddle and head of two ravines, about 50 lks. W. of line, draining SE. and N.

6.50 Desc. steep general NW. slope 340 ft. to

25.65 Rocky spur, projects N. 30° W.  
Desc. steep rocky NE. slope 440 ft. to 45.35 chs.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground to bedrock, with a limestone, 10x7x2 ins., mkd. X, deposited at the base, and in a mound of stone, for the ¼ sec. cor., with brass cap mkd.