

SUBDIVISIONS OF T. 23 N., R. 34 E.

Chains	Thence over mountainous bench land.
	Desc. rocky NW. slope 50 ft. to
59.90	Main wash from canyon, 25 lks. wide, 15 ins. deep, (in bend) drains NW. from NE.
	Asc. gravelly NE. slope 30 ft. to
65.40	Desc. along N. slope over numerous shallow ravines 35 ft. to
85.66	Intersect W. bdy. of Tp., N. 0° 06' E., 78 lks. from the cor. of secs. 12 and 13, and at point of intersection; set an iron post, 3 ft. long, 2 ins. diam., 14 ins. in the ground to bedrock, with a granite stone, 6x6x5 ins., mkd. X, deposited at the base, and in a mound of stone, for the closing cor. of secs. 7 and 18, with brass cap mkd.
	Land, E. 54 chs. rough mountainous, W. 32 chs. bench. Soil, rocky on upper slopes, gravelly in lowlands, 3rd and 4th rate. Timber, none. Undergrowth, sagebrush, shadscale, greasewood. General drainage, NW. Grazing, poor.
	N. 0° 03' W., bet. secs. 7 and 8.
	Over mountainous land, through scattering undergrowth.
	Asc. rocky SW. slope 10 ft. to
1.80	Spur, projects N. 40° W.
	Desc. rocky general NE. slope 260 ft. to 18.75 chs.
13.95	Ravine, drains N. 65° W.
15.40	Spur, projects N. 75° W.
18.75	Main ravine, with wash, 40 lks. wide, 3 ft. deep, drains S. 60° W.
	Asc. steep rocky broken SE. slope 180 ft. to
30.60	Spur, bears S. 50° W.
	Desc. rocky NW. slope 290 ft. to 47.60 chs.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground to bedrock, with a granite stone, 5x4x3 ins., mkd. X, deposited at the base, and in a mound of stone, for the $\frac{1}{4}$ sec. cor., with brass cap mkd.