


SUBDIVISION OF T. 23 N., R. 34 E.

Chains

85.33

Intersect W. bdy. of Tp., N. 0° 06' E., 28 lks. from the cor. of secs. 1 and 12; and at point of intersection set an iron post, 3 ft. long, 2 ins. diam., 20 ins. in the ground to bedrock, with a granite stone, 6x4x2 ins., mkd. X, deposited at the base, and in a mound of stone, for the closing cor. of secs. 6 and 7, with brass cap mkd.



Land, rolling mountainous bench land. Soil, gravel, 3rd rate. Timber, none. Undergrowth, sagebrush, shadscale, greasewood. General drainage, NW. Grazing, poor.

N. 0° 03' W., bet. secs. 5 and 6.


Over rolling mountainous benchland.

Desc. general NW. slope 95 ft. to 57.90 chs.

10 Bottom of draw, drains NW.

13.90 Draw, drains W.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 10 ins. in the ground to bedrock, with a granite stone, 6x3x3 ins., mkd. X, deposited at the base, and in a mound of stone, for the 1/4 sec. cor., with brass cap mkd.



52.10 Wash, 10 lks. wide, 6 ins. deep, drains S. 40° W.

57.90 Desc. broken rocky NE. slope 100 ft. to

65.65 Bottom of ravine, drains N. 75° W.

Asc. steep rocky SW. slope 40 ft. to

66.80 Spur, projects W.

Desc. rocky NW. slope 40 ft. to

70.25 Ravine, drains S. 40° W.

Asc. rocky general SE. slope 15 ft. to

72.00 General descent of 10 ft. to

80.08 Intersect N. bdy. of Tp., N. 89° 57' W., 14.96 chs. from the cor. of secs. 31 and 32, and at point of intersection; set an iron post, 3 ft. long, 2 ins. diam., 16 ins. in the ground to bedrock, with granite stone, 5x4x2 ins., mkd. X, deposited at the base, and in a mound of stone, for the closing cor. of secs. 5 and 6, with brass cap mkd.