

T. 21 N., R. 20 E.

Chains

DEPENDENT RESURVEY OF A PORTION OF THE EAST BDY.
OF T. 21 N., R. 20 E.

Reestablishment of a portion of survey executed by
A. J. Hatch, U. S. Deputy Surveyor, in 1867 under
Contract No. 6.

The original cor. of secs. 13, 18, 19 and 24 on the E.
bdy. of the Tpl. is a granite stone, 7x7x10 ins. above
ground, firmly set in the center of an old mound of
earth and stone, marked with 3 notches on N. and S. edges.

At point for cor.

Set an iron post, 3 ft. long, 2 ins. diam., 20 ins. in
the ground to solid rock, over a cross (X), with the
original stone deposited at the base, and in a mound of
stone, 4 ft. base, 1 ft. high, for cor. of secs. 13, 18,
19 and 24, with brass cap mkd.

T21N
R20E R21E

S13 | S18

—|—
S24 | S19

1935

Thence

N. 0° 59' E., bet. secs. 13 and 18.

Over rolling broken hilly land through medium dense under-
growth.

.30 Old road, bears S. 80° W. and E.

Asc. along general W. slope crossing heads of numerous
draws draining W.

24.00 Base of rocky SW. slope, bears NW. and SE., asc. 80
ft. through scattering timber.

30.00 Low spur, slopes S. 70° W., continue to ascend along a
W. slope.

37.90 Top of ascent of W. slope of small rounded knoll.
Desc. 20 ft. along a broken W. slope.

40.38 The $\frac{1}{4}$ sec. cor. of secs. 13 and 18, which is a granite
stone, 6x8x12 ins. above ground, firmly set in the
center of an old embedded mound of stone. No distinct
chisel marks are discernible. As this monument agrees
very closely with the record as to size and as it has
the same general appearance of weathering as other iden-
tified corners during this survey, it is accepted as
being the original corner.

At point for cor.

Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in
the ground to solid rock, over a cross (x) with the
original stone deposited at the base, and in a mound
of stone, 3 ft. base, 1 ft. high, for $\frac{1}{4}$ sec. cor., with
brass cap mkd.