

SUBDIVISION OF FRAC. T. 33 S., R. 66 E.

Chains	General descent.
77.30	Spur, projects E.
	Desc. 150 ft. to
80.90	Intersect 8th stan. par. S.
	Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for the closing cor. of secs. 5 and 6, with brass cap mkd.
	T32S R66E
	S31
	S6 S5
	T33S R66E
	CC
	1932
	raise a mound of stone, 4 ft. base, 3 ft. high, S. of cor.
	Cor. stands near head of abrupt gravelly gully and on abrupt NE. face of spur.
	From this point the stan. cor. of secs. 31 and 32, hereinafter described, bears N. 89° 23' E., 19.74 chs. dist.
	Land, S. 17.42 chs. rolling bench, N. 63.58 chs. rough broken hills, general E. and SE. exposure.
	Soil, sand, gravel and clay, 2nd and 3rd rate.
	Timber, none.
	Undergrowth, scattering creosote brush, chaparral cactus and weeds.
	Grazing, none.
	From the cor. of secs. 7, 8, 17, and 18.
	East, bet. secs. 8 and 17 on auxiliary base line.
	Over rolling bench land sloping gently to E. and SE., through medium creosote brush, chaparral, scattering cactus and weeds.
	General descent of 195 ft. to sec. cor.
34.65	Road, bears N. 50° W. and S. 50° E.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with a quartzite stone, 4x4x3 ins., mkd. X, deposited at the base, for the 1/4 sec. cor., with brass cap mkd.
	S8
	1/4
	S17
	1932
	dig pits, 18x18x12 ins., E. and W. of post, 3 ft. dist.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for the cor. of secs. 8, 9, 16, and 17, with brass cap mkd.