

SURVEY OF W. BDY. FRAC. T. 31 S., R. 66 E.

Chains	North, bet. secs. 1 and 6.
	Over rough mountainous land through scattering undergrowth.
	Steep descent of 40 ft. to
2.00	Draw, drains E.
	Steep ascent of S. slope 35 ft. to
4.40	Spur, projects SE. about 5 chs.
	Desc. steep N. slope 40 ft. to
8.35	Draw, drains SE. about 8 chs. to junction with ravine, thence NE.
	Abrupt ascent of rocky S. slope 230 ft. to
18.35	Spur, projects E.
	Steep descent of N. slope 65 ft. to
20.75	Draw, drains S. 80° E.
	Abrupt ascent of S. slope 200 ft. to
34.10	Spur, projects E.
	Desc. NE. slope 570 ft. to 61.30 chs.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for the $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4}$
	S1 S6
	1932
	raise a mound of stone, 3 ft. base, 2½ ft. high, W. of cor.
46.60	Begin precipitous descent of N. slope.
61.30	Enter east edge of canyon bottom at bend, drains N. 10° W. from SW.
	Asc. along W. slope 80 ft. to
66.55	Rocky point on W. slope, projects W. about 2 chs., small spring at end of point.
	Desc. NW. slope 90 ft. to
70.20	Canyon, drains NE. Small seepage springs, locally known as Iron Pipe Springs, in bottom about 2 chs. S. 15° W.
	Abrupt ascent of rocky S. slope 125 ft. to
74.90	Spur, projects E.
	Desc. gradual to precipitous N. slope 560 ft. to junction of draws.
77.70	Begin precipitous descent.