

DEPENDENT RESURVEY 4TH STAN. PAR. S., S. BDY. T. 16 S., R. 70 E.

Chains
40.00

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground for the reestablished standard $\frac{1}{4}$ sec. cor., with brass cap mkd.

SC
1835

1932

of stone, 4 ft. base, 3 ft. high, N. of the cor. raise a mound

Continue over rolling hills; desc. 10 ft.

41.90 Wash, drains SW.; asc. 35 ft. over a W. slope.

46.90 Spur, projects SW.; desc. 15 ft.

47.90 Draw, drains SW.; asc. 40 ft. over a W. slope.

53.40 Spur, projects SW.; desc. 35 ft.

57.40 Leave hills and enter large flood basin, draining SW.; desc. 35 ft. over a SE. slope.

78.60 Draw, drains SW.

Leave flood basin and enter rolling hills.

Diff. bet. meas. of 80.00 chs., by two sets of chainmen, is 4 lks.; the position of the middle point:

By 1st set, 80.02 chs.

By 2nd set, 79.98 chs.; the mean of which is:

80.00 On the secant,

Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground for the reestablished standard cor. of secs. 35 and 36, with brass cap mkd.

SC
T16SR70E
S35 | S36

1932

Deposit a limestone rock 8x8x3 ins. mkd. with a cross (X), at the base of the post and raise a mound of stone, 3 ft. base, 2 ft. high, N. of the cor.

Land, rolling hills; SW. exposure and drainage. Soil, gravelly clay. Limestone boulders; 3rd rate. Undergrowth, creosote, blackbrush, chaparral, mountain rush and cacti. No timber. Poor grazing.

East, with the reestablishment of the 4th standard parallel South, along the S. bdy. of sec. 36, on a transit line describing the secant and which bears S. 89°58.7' E.

Over rolling bench land, having a SW. slope, through scattering undergrowth; asc. 20 ft.

6.70 Spur, projects S. about 7 chs.; thence SW.; desc. 15 ft.