

## INDEPENDENT RESURVEY, RANGE LINE THROUGH T. 16 S., BET. RS. 70 &amp; 71 E.

## Chains

INDEPENDENT RESURVEY OF THE RANGE LINE THROUGH T. 16 S.,  
BETWEEN RS. 70 AND 71 E.

Independent resurvey, superseding the survey executed by  
Woods and Myrick, U. S. Deputy Surveyors in 1881.

Beginning at the reestablished standard cor. of T. 16 S.,  
Rs. 70 and 71 E., an iron post, 3 ins. diam., mkd. and  
witnessed as described in this Book.

North, on true line, bet. secs. 31 and 36.

Over rolling hills through scattering undergrowth; asc.  
70 ft. along a SE. slope.

1:10 Spur, projects S. 85° W.; desc. 95 ft. along a NW. slope.

10.84 Draw, drains SW.; asc. 140 ft. along a SE. slope.

32.90 Spur, projects SW.; desc. 10 ft. over a NW. slope.

37.90 Draw, drains SW.; asc. 10 ft.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in  
the ground, for the reestablished  $\frac{1}{4}$  sec. cor., with brass  
cap mkd.

$\frac{1}{4}$   
S36 | S31

1933

raise a mound  
of stone, 3 ft. base, 2 ft. high, W. of the cor.

This cor. is situated on a general W. slope.

Asc. 175 ft. over a general S. slope to the spur.

59.50 Large wash, drains SW.; continue ascent.

67.20 Spur, projects SW.; desc. 45 ft. along a NW. slope.

71.00 Small gulch, drains SW.; asc. 40 ft. along a SW. slope.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 14 ins. in  
the ground to solid rock and over a cross (X), in a mound  
of stone for the reestablished cor. of secs. 25, 30, 31,  
and 36, with brass cap mkd.

T16S  
R70E R71E  
S25 | S30

S36 | S31  
1933

This cor. is situated on the W. point of a spur, project-  
ing from the NE.

Land, rolling hills; general SW. exposure and drainage.

Soil, sand, clay and gravel; 3rd rate.

Undergrowth, creosote brush, blackbrush, mountain rush,