

INDEPENDENT RESURVEY, RANGE LINE THROUGH T. 16 S., BET. RS. 70 & 71 E.

Chains

North, bet. secs. 1 and 6.

Over rough mountainous land, through medium undergrowth; asc. 80 ft. along a SW. slope.


2.80 Ridge, bears NW. and SE.; asc. 290 ft. along a SE. slope to the spur.

10.65 Enter scattering juniper and pinon timber; bears NW. and SE.; continue along a broken SE. slope.

26.00 Spur, projects S. 70° E.; desc. 25 ft. along a NE. slope.

32.80 Draw, drains S. 70° E.; asc. 245 ft. along a SW. slope.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground to solid rock and in a mound of stone for the reestablished 1/4 sec. cor., with brass cap mkd.



1933

from which

A juniper, 8 ins. diam., bears N. 4°30' E., 75 lks. dist., mkd. 1/4S6BT.


A juniper, 6 ins. diam., bears N. 29°15' W., 67 lks. dist., mkd. 1/4S1BT.

This cor. is situated on the top of a small spur projecting SE.

Asc. 690 ft. over a broken SE. slope.

72.20 Spur, projects E.; desc. 30 ft. along a NE. slope.

80.00 Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the ground to solid rock and in a mound of stone for the reestablished cor. of Tps. 15 and 16 S., Rs. 70 and 71 E., with brass cap mkd.



T16S

1933

from which

A juniper, 4 ins. diam., bears N. 27°45' E., 47 lks. dist., mkd. T15SR71ES31BT.

A pinon, 6 ins. diam., bears S. 79° E., 72 lks. dist., mkd. T16SR71ES6BT.

A juniper, 3 ins. diam., bears S. 15°45' W., 24 lks. dist., mkd. BT only.

A juniper, 10 ins. diam., bears N. 44° W., 44 lks. dist., mkd. T15SR70ES36BT.

This cor. is situated on a steep and rocky NE. slope.

Land, rough and broken mountains; general SE. exposure and drainage.

Soil, sandy to gravelly loam; 3rd rate.