

## E. Dependent Resurvey of the South Boundary of T. 5 S., R. 38 E.

Chains

 $\frac{1}{4}$ S32

1933

Thence:

S.  $89^{\circ} 45'$  W., on true line along the south boundary of sec. 32,

Along a general SW. slope.

35.50 Road, bears N.  $70^{\circ}$  W. to Oasis, California, and SE. to Lida, Nevada.

39.05 Point 80.00 chains in departure from the cor. of secs. 4 and 5.

Set an iron post, 3 ft. long, 2 ins. diameter, 30 ins. in the ground, with a quart of broken glass deposited at the base, for cor. of secs. 5 and 6 only, with brass cap mkd:

T5S R38E

S32

S6 | S5

T6S

1933

39.83 The original cor. of secs. 5, 6, 31, and 32, mkd. by a basalt stone, 10x8x6 ins., set in a mound of stone, and mkd. with 5 notches upon the east edge and 1 notch upon the west edge.

At point for cor.

Set an iron post, 3 ft. long, 2 ins. diameter, 20 ins. in the ground to solid rock, with the original stone deposited at the base, and in a mound of stone, for cor. of secs. 31 and 32 only, with brass cap mkd:

T5SR38E

S31 | S32

S6

T6S

1933

Land, rolling mountains, SW. exposure and drainage.  
Soil, sandy to gravelly loam, 2nd rate.  
Timber, none; undergrowth, sagebrush and buckbrush.  
Grazing, fair.

## Survey of the North Boundary of T. 6 S., R. 38 E.

West, on true line on north bdy. Sec. 6.

Over nearly level land, through a medium dense undergrowth.

24.90 Wash, 15 lks. wide, 5 ft. deep, drains N.  $60^{\circ}$  W.39.22 Set an iron post, 3 ft. long, 1 in. diameter, 30 ins. in the ground, with a limestone rock, 8x6x4 ins., mkd. X, deposited at the base, for  $\frac{1}{4}$  sec. cor. of sec. 6, with brass cap mkd: