


## Chains

Soil, shallow gravelly loam, 3d rate.  
 Timber, pinon and juniper; undergrowth; sagebrush, buck  
 brush and mountain rush, bunch grass.  
 Grazing, fair.

South, between secs. 25 and 26.

Over mountainous land, through a dense timber and a scant  
 undergrowth; asc. 100 ft. over a N. slope.

- 3.90 Spur, projects NW.; desc. 50 ft. along a SW. slope.  
 10.70 Draw, drains NW.; asc. 390 ft. along a NE. slope.  
 25.77 Point on the top of a ridge bearing NE. and SW.; desc.  
 along a steep SE. slope.  
 40.00 Point for the  $\frac{1}{4}$  sec. cor. falls in the head of a draw  
 draining SE. and in steeply sloping rock where the monu-  
 ment can not be erected: Asc. 330 ft. along a steep  
 and rocky NE. slope.  
 50.00 Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the  
 ground to solid rock, and in a mound of stone, for the  
 witness  $\frac{1}{4}$  sec. cor., with brass cap mkd:



from which

A pinon, 3 ins. diam., bears N.  $32^{\circ} 15'$  E., 53 lks.  
 dist., mkd. BT.

A pinon, 8 ins. diam., bears N.  $56^{\circ} 15'$  W., 64 lks.  
 dist., mkd.  $WC\frac{1}{4}S26BT$ .

Cor. is located on a steep N. slope.

Asc. 120 ft. along a N. slope.

- 52.87 Spur, projects E.; desc. 50 ft. along a SE. slope.  
 57.80 Draw, drains E.; asc. 80 ft. along a NE. slope.  
 59.97 Point on the top of a spur projecting E.; desc. 190 ft.  
 along a SE. slope.  
 66.80 Draw, drains SE., heading about 2 chains NW.; asc. 70 ft.  
 along a NE. slope.  
 69.50 Spur, projects SE.; desc. 300 ft. over a steep and rocky  
 S. slope.  
 77.09 Intersect the Nevada-California State line at a point  
 4.59 chains S.  $47^{\circ} 23'$  E. of the  $\frac{1}{2}$  mile post between  
 Monuments 79 and 80, heretofore described:  
 At point of intersection:  
 Set an iron post, 3 ft. long, 2 ins. diameter, 30 ins.