

INDEPEND. RESURVEY OF THE 2ND STAN. PAR. N. ALONG S. BDY. OF T. 11 N., R. 44 E.

Chains	
	East, along the S. bdy. of sec. 36, on a transit line describing the tangent; which bears S. 89°58.6' E.
	Over mountainous land; through medium dense timber and undergrowth; asc. 395 ft. along a NW. slope.
17.85	Ridge, bears NW. and SE.; desc. 225 ft.
25.60	Head of a small draw, drains SE.
	Timber becomes scattering; asc. 100 ft.
30.90	Top of spur, projects SE.; desc. 230 ft. to the 80.00 chain point.
39.00	Bottom of canyon, drains S.; old road in bottom.
40.00	North 5 lks. from the tangent, Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for standard $\frac{1}{4}$ sec. cor., with brass cap mkd.
	SC
	<u>$\frac{1}{4}$ S 36</u>
	1933
	from which
	A pinon, 12 ins. diam., bears N. 40°06' E., 170 lks. dist., mkd. $\frac{1}{4}$ S36SCBT.
	A pinon, 6 ins., diam., bears N. 13°30' W., 78 lks. dist., mkd. $\frac{1}{4}$ S36SCBT.
41.80	Asc. a NW. slope through medium dense timber and undergrowth.
55.73	Enter scattering mahogany.
69.95	Top of ridge bears N. and S.; desc. a SE. slope through scattering timber and undergrowth, 145 ft.
80.00	North, 7 lks. from the tangent, Set an iron post, 3 ft. long, 3 ins. diam., 8 ins. in the ground, and in a mound of stone to top for standard cor. of Tps. 11 N., Rs. 44 and 45 E., with brass cap mkd.
	SC
	T11N
	R44E R45E S36 S31
	1933
	Deposit a stone, 8x4x4 ins., mkd. with a cross (X) at base of post.
	Land, mountainous.
	Soil, rocky; 4th rate.
	Undergrowth, black sage.
	Timber, juniper and pinon.