

COMPLETION OF THE SUBDIVISION OF T. 11 N., R. 44 E.

Chains

68.65 Spur, projects W.

74.25 Draw, drains W.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 6 ins. in the ground to bedrock, mkd. (X) at point for cor., and in a large mound of stone to top, for cor. of lots 1 and 8 for sec. 3, and lots 4 and 5, sec 2, with brass cap mkd.

T11NR44E

S3	1 4	S2
	8 5	

1936

87.65 Intersect the S. bdy. of T. 12 N.; R. 44 E.

Set an iron post, 3 ft. long, 2 ins. diam., 4 ins. in the ground to bedrock, mkd. with a cross (X) at point for cor., and in a mound of stone to top, for closing cor. of secs. 2 and 3, with brass cap mkd.

T12NR44E

S35

S3		S2
----	--	----

T11NR44E

CC

1936

From this point of intersection the reconstructed cor. of Secs. 34 and 35 on the S. bdy. of T. 12 N., R. 44 E., bears N. 89°57' W., 7.15 chs. dist.

Land, mountainous.

Soil, gravelly; 3rd rate.

Undergrowth, sagebrush, shadscale and rabbit brush.

Timber, none.

At midpoint bet. the closing sec. cors. on the N. bdy. sec. 2.,

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for $\frac{1}{4}$ sec. cor., for sec. 2 only, with brass cap mkd.

 $\frac{1}{4}$ S 2

1936

raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.

From this cor.; the $\frac{1}{4}$ sec. cor. on S. bdy. sec. 35, T. 12 N., R. 44 E., bears N. 89° 53' W., 7.075 chs. dist.

From the standard cor. of secs. 33 and 34 on the S. bdy. of the township, heretofore described.

N. 0°02' W., bet. secs. 33 and 34.

Over mountainous land, through medium dense undergrowth; asc. a rocky slope 160 ft.