

Old corners renewed with iron posts but not ~~mentioned~~ described in the resurvey field notes. These descriptions have been copied from the engineer's field tablets.

(1)

Set an iron post 3 ft. long 2 ins. diam. 30 ins. in the ground, and in mound of earth, for cor. of secs. 19, 24, 25 and 30 with brass cap mkd.

T 11 N
R 43 E R 44 E
S 24 | S 19

S 25 | S 30
1933

(2)

Set an iron post 3 ft. long 1 in. diam. 30 ins. in the ground, with broken glass deposited at base for $\frac{1}{4}$ sec. cor. with brass cap mkd.

$\frac{1}{4}$
S 25 | S 30
1933

(3)

Set an iron post 3 ft. long 2 ins. diam. 30 ins. in the ground for cor. of secs. 25, 30, 31 and 36, with brass cap mkd.

T 11 N
R 43 E R 44 E
S 25 | S 30

S 36 | S 31
1933

raise a mound
of stone 3 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

(4)

Set an iron post 3 ft. long 1 in. diam. 30 ins. in the ground for $\frac{1}{4}$ sec. cor. with brass cap mkd.

$\frac{1}{4}$
S 36 | S 31
1933

raise a mound
of stone 3 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

(5)

Set an iron post 3 ft. long 1 in. diam. 16 ins. in the ground and in mound of stone to top for $\frac{1}{4}$ sec. cor. with brass cap mkd.

S 19
 $\frac{1}{4}$ -----
S 30
1933