4-673 b

Chains	PALCO)
39.56	On the top of a solid rocky spur in a hole drilled 15 ins. into the rock; set a 24 in. section of the regulation 1 in. iron post, for witness \(\frac{1}{4} \) sec. cor., with brass cap mkd.
	. Tana C. Lessa Lord are Would be J. E. 149.08 .8
300	reconstant sections of the section of the sections of the section
4 .	dala 12 a novo . on de 1932; DE aniant sunto A 00.15
•	of stone, 3 ft. base, 2 ft. high, W. of post.
mi .mi	
40.00	True point for 4 sec. cor. falls on a steep rocky N. slope, impracticable to establish cor.
43.10	Head of a draw, drains SW.; asc. 115 ft. along a SW. slope.
46.90	High spur, projects W.; desc. 140 ft. along a NW. slope.
52.60	Draw, drains W.; asc. 20 ft. along a SW. slope.
62.50	Spur, projects W.; desc. 240 ft. to the closing cor.
66.20	Draw, drains W.; continue along a W. slope.
79.98	Intersect N. bdy. of the Tp., at a point 61 lks. West of the original cor. of secs. 5, 6, 31, and 32, which is an iron post, 3 ins. diam., firmly set, mkd. and witnessed, as described in the official records.
	At point of intersection Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground for closing cor. of secs. 5 and 6, T. 29 N., R. 21 E., with brass cap mkd.
ACTIVA NEXT	T30N R21E
	s6 s5

S6 | S5 CC T29N R21E 1932

.becle

of stone, 2 ft. base, $l\frac{1}{2}$ ft. high, W. of the cor. The ground immediately S. of the cor. is too steep to permit the erection of the mound in this direction.

The original cor. of secs. 5, 6, 31, and 32, on the S. bdy. of T. 30 N., R. 21 E., is altered and refers to secs. 31 and 32, T. 30 N., R. 21 E. only; therefore with brass cap remarked

T30N R21E S31 S32 T29N R21E 85 1932 Smir, Jordjeter 1.1

Erect a large mound of stone around the cor.

Land, rolling mountainous; NW. exposure and drainage. Soil, fine sandy volcanic ash and heavy yellow clay;