

DEPENDENT RESURVEY EAST BDY. T. 19 S., R. 62 E.

Chains

From the $\frac{1}{4}$ sec. cor.,
North, with continuous measurement.

80.30

Fall 16 lks. E. of the cor. of secs. 7, 12, 13, and 18,
hereinafter described.
The bearing of this half mile is N. $0^{\circ}14'$ W., and the
distance is 40.09 chs.

From the cor. of secs. 7, 12, 13, and 18,
North, bet. secs. 7 and 12.

40.30

Fall 21 lks. E. of the $\frac{1}{4}$ sec. cor., hereinafter described.
The bearing of this half mile is N. $0^{\circ}18'$ W., and the
distance is 40.30 chs.

From the $\frac{1}{4}$ sec. cor.,
North, with continuous measurement.

80.68

Fall 8 lks. E. of the cor. of secs. 1, 6, 7, and 12, here-
inafter described.
The bearing of this half mile is N. $0^{\circ}07'$ W.,
and the distance is 40.38 chs.

From the cor. of secs. 1, 6, 7, and 12,
North, bet. secs. 1 and 6.

40.24

Fall 13 lks. E. of the $\frac{1}{4}$ sec. cor., hereinafter described.
The bearing of this half mile is N. $0^{\circ}11'$ W., and the
distance is 40.24 chs.

From the $\frac{1}{4}$ sec. cor.,
North, with continuous measurement.

80.79

Fall 2 lks. W. of the cor. of Tps. 18 and 19 S., Rs. 62
and 63 E., hereinafter described.
The bearing of this half mile is N. $0^{\circ}02'$ E., and the
distance is 40.55 chs.

True Lines.

The cor. of Tps. 19 and 20 S., Rs. 62 and 63 E. is a sand-
stone, 14x10x4 ins., above ground, firmly set in the
center of an old embedded mound of stones, marked 6
grooves on N., E., S., and W. faces.

At cor. point,

Set an iron post, 3 ft. long, 3 ins. diam., 30 ins. in the
ground, with original monument alongside, for the cor. of
Tps. 19 and 20 S., Rs. 62 and 63 E., with brass cap marked

T19S

R62E R63E

S 36 S 31

S 1 S 6

T20S

1930

raise a mound of
stone, 6 ft. base, 3 ft. high, S. of cor.

From the cor.,

Las Vegas Airport Beacon light bears S. $86^{\circ}21'$ W.

"Apex" beacon light bears N. $25^{\circ}11'$ E.