

56

DEPENDENT RESURVEY EAST BDY. T. 19 S., R. 62 E.

Chains

At cor. point,

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with original monument alongside, for $\frac{1}{4}$ sec. cor. of sec. 12 only, with brass cap mkd.

S 12

1930

raise a mound of

stone, 3 ft. base, $2\frac{1}{2}$ ft. high, W. of cor.

Thence

N. $0^{\circ}07'$ W., with continuous measurement.

60.90 Wash, course S. 60° W.68.00 Small wash, course S. 30° W.

80.68 The cor. of secs. 1, 6, 7, and 12, which is a limestone, $10 \times 7 \times 7$ ins., firmly set, in a mound of stone, marked 5 notches on S. edge, 1 notch on N. edge.

At cor. point,

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with original monument alongside, for the cor. of secs. 1 and 12 only, with brass cap mkd.

T19S

R62E

R63E

S 1

S 6

S12

1930

raise a mound of stone, 4 ft. base, 3 ft. high, W. of cor. This cor. stands on low flat bench 110 ft. above dry wash at 32.50 chs. this mile. A frame house on W. slope bears S. $82^{\circ}36'$ E.

Land, gently rolling.

Soil, shallow rocky loam, 3rd and 4th rate.

Undergrowth, creosote brush, greasewood, cacti.

No timber.

N. $0^{\circ}11'$ W., along the east bdy. of sec. 1.

Over rolling bench land, through medium dense undergrowth. Asc. gradual, uniform S. slope.

14.20 Dry wash, 50 lks. wide, 6 to 8 ft. deep, drains SE.

32.00 Leave bench land, bears NE. and SW. 5 chs., thence northerly; asc. broken hilly land.

40.24 The $\frac{1}{4}$ sec. cor., which is a limestone, $18 \times 10 \times 8$ ins., set in a mound of stone over exposed surface ledge, marked $\frac{1}{4}$ on W. face.

At cor. point,

Cut a drill hole 3 ins. in solid rock in which I set an