

Chains

Chains	Description										
	<p>REESTABLISHMENT OF SURVEYS EXECUTED BY W. H. MYRICK, U. S. DEPUTY SURVEYOR IN 1882.</p> <p>From the reestablished cor. of Tps. 19 and 20 S., Rs. 63 and 64 E., heretofore described.</p> <p>North, on true line bet. secs. 31 and 36.</p> <p>Over rolling and broken low hills, through medium dense undergrowth.</p> <p>Asc. 80 ft. to $\frac{1}{4}$ sec. cor.</p>										
34.00	Enter low bench lands, sloping S., bear NW. and NE.										
40.00	Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to solid rock, with a limestone, 10x6x3 ins. marked cross (X) at base of post, for the $\frac{1}{4}$ sec. cor. of secs. 31 and 36, with brass cap mkd.										
	$\frac{1}{4}$ <table style="margin: auto;"> <tr> <td>S36</td> <td style="border-left: 1px solid black; border-right: 1px solid black; padding: 0 5px;">S31</td> </tr> <tr> <td colspan="2" style="text-align: center;">1933</td> </tr> </table> <p style="text-align: center;">raise a mound of stone, 4 ft. base, around post to top.</p>	S36	S31	1933							
S36	S31										
1933											
42.90	Shallow gravelly dry wash, 30 lks. wide, drains SW., continue ascent of 60 ft. over uniform SW. slope.										
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for the cor. of secs. 25, 30, 31, and 36, with brass cap mkd.										
	<table style="margin: auto;"> <tr> <td colspan="2" style="text-align: center;">T19S</td> </tr> <tr> <td>R63E</td> <td style="border-left: 1px solid black; border-right: 1px solid black; padding: 0 5px;">R64E</td> </tr> <tr> <td>S 25</td> <td style="border-left: 1px solid black; border-right: 1px solid black; padding: 0 5px;">S 30</td> </tr> <tr> <td colspan="2" style="border-top: 1px solid black; text-align: center;">1933</td> </tr> <tr> <td>S 36</td> <td style="border-left: 1px solid black; border-right: 1px solid black; padding: 0 5px;">S 31</td> </tr> </table> <p style="text-align: center;">raise a mound of stone, 4 ft. base, 3 ft. high, W. of cor.</p> <p>Land, rolling low hills and broken bench land.</p> <p>Soil, sandy and gravelly clay loam, shallow, 3rd rate.</p> <p>Undergrowth, creosote, greasewood, shadscale, cacti.</p> <p>No timber.</p>	T19S		R63E	R64E	S 25	S 30	1933		S 36	S 31
T19S											
R63E	R64E										
S 25	S 30										
1933											
S 36	S 31										
	<p>North, bet. secs. 25 and 30.</p> <p>Over broken bench land, through medium dense undergrowth; asc. gradual SW. slope.</p>										
16.50	Shallow drain, course S. 30° W.										
33.00	Dry wash, 6 lks. wide, 1 ft. deep, drains SW.										
40.00	On north side of top of small flat spur, 80 ft. above cor., projecting SW.,										
	<p>Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for the $\frac{1}{4}$ sec. cor., with brass cap mkd.</p>										