

62.3 20 25 . DEPENDENT RESURVEY OF THE EAST BDY. T. 19 S., R. 63 E.

Chains	
31.80	Low spur, projects SW. about 5 chs.
35.90	Draw, drains S. 30° W.
40.00	On broken S. slope, 40 ft. above draw, Set an iron post, 3 ft. long, 1 in. diam., 14 ins. in the ground to solid rock with a limestone, 10x8x6 ins. marked with a cross (X) at base of post, for $\frac{1}{4}$ sec. cor. with brass cap marked
	<div style="text-align: center;"> $\frac{1}{4}$ S 12 S 7 1933 </div> raise a mound of stone, 4 ft. base, to top of post.
	Asc. broken S. slope.
67.60	Large draw, drains S. 40° W.; asc. 70 ft.
80.00	Set an iron post, 3 ft. long, 3 ins. diam., 26 ins. in the ground, for the cor. of secs. 1, 6, 7, and 12, with brass cap marked
	<div style="text-align: center;"> T19S 01 R63E R64E S 1 S 6 S 12 S 7 1933 </div> raise a mound of stone, 4 ft. base, 2 ft. high, W. of cor.
	Land, broken, hilly.
	Soil, clay loam, 3rd and 4th rate.
	Undergrowth, creosote, cacti.
	No timber.
	North, bet. secs. 1 and 6.
	Over rolling broken land, through medium dense undergrowth.
10.00	Spur, projects S. 30° W., continue along broken W. slope.
26.80	Asc. along W. side of spur.
34.00	Spur, same one as noted at 10.00 chs., 160 ft. above cor., projects S. from NW.; desc. NE. slope.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 16 ins. in the ground to solid rock and in large mound of stone, with a sandstone 6x5x4 ins. marked with a cross (X) at base of post, for $\frac{1}{4}$ sec. cor., with brass cap marked
	<div style="text-align: center;"> $\frac{1}{4}$ S 1 S 6 1933 </div>
43.00	Head of small gully, drains S. 30° E.; asc. steep rocky S. slope 160 ft. over rough, broken limestone ledges, facing S. and bearing E. and W.