

SURVEY OF THE N. BDY. T. 19 S., R. 63 E.

Chains

80.00

Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. to solid rock, with limestone, 8x6x4 ins., marked cross (X), deposited at base of post, for cor. of secs. 5, 6, 31, and 32, with brass cap mkd.

T18S	R63E
S 31	S 32
S 6	S 5
T19S	
1933	

raise a mound of stone, 4 ft. base, 3 ft. high, W. of cor.

Land, broken to rough mountainous.
Soil, shallow rocky loam; 3rd and 4th rate.
Undergrowth, creosote, buckbrush, cacti.
No timber.

West, on true line, bet. secs. 6 and 31.

Over rough mountainous land, through scattering undergrowth. Asc. steep, rocky E. slope, 180 ft.

4.65

Along N. side of prominent outcrop on high butte on divide bearing NE. and SW.; desc. 80 ft. over rocky N. slope.

12.30

Main divide, bears N. and S. 60° W.; desc. over rocky NW. slope, 380 ft. along top of spur.

33.00

Rocky spurs, project SW. and N. 60° W.; desc. 130 ft. over W. slope.

40.00

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground for $\frac{1}{4}$ sec. cor., with brass cap mkd.

S 31
$\frac{1}{4}$
S 6
1933

raise a mound of stone, 4 ft. base, 3 ft. high, N. of cor.

This corner is situated on small rocky spur, projecting SW.

Descend along rocky S. slope.

51.60

Rocky spur, projects S. 60° W.; desc. NW. slope.

62.75

Junction of washes from N. and N. 50° E., draining S. and at foot of mountainous W. slope, 320 ft. below $\frac{1}{4}$ sec. cor., bearing N. 60° E. and S.; continue over broad flat basin.

69.84

Intersect the E. bdy. of T. 19 S., R. 62 E., S. 0°02' W., 4.13 chs. distant from the cor. of Tps. 18 and 19 S., R. 62 E., hereinbefore described.

At point of intersection,

Set an iron post, 3 ft. long, 3 ins. diam., 21 ins. in the ground to solid rock over a cross (X) at exact