

SUBDIVISION OF T. 19 S., R. 63 E.

Chains

This corner is situated on S. slope in high creosote brush.

Across sand dune hills, through high creosote brush; desc. 11 ft.

69.29

Intersect W. bdy. of Tp. S. 0° 34' E., 97 lks. dist. from the cor. of secs. 25 and 36, R. 62 E., heretofore described.

At point of intersection,

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for the closing cor. of secs. 30 and 31, with brass cap mkd.

T19S

R62E R63E

S30 C

S36

S31 C

1933

raise a mound

of stone, 4 ft. base, 2 ft. high, E. of cor.

Land, sand dune hills.

Soil, sand and gravel; 4th rate.

Undergrowth, creosote, buckbrush. Sand grass.

Grazing, poor.

From the cor. of secs. 29, 30, 31, and 32.

N. 0° 03' W. bet. secs. 29 and 30.

Asc. 81 ft. on S. slope over sand dune hills, through scattered undergrowth.

40.00

Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground, with a limestone 4x4x6 ins. mkd. with a cross (X), deposited at base, in a mound of stone, for 1/4 sec. cor, with brass cap mkd.

1/4

S30 S29

1933

This corner is situated on E. slope of sand hill and W. side of sandy draw with SW. course.

Over sand dune hills; asc. 21 ft.

49.50

Sand benchland; desc. 59 ft.

60.60

Wash, course SW.; asc. 97 ft. over sand hills.

80.00

Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground to solid rock, with broken glass and a rock 10x8x6 ins. mkd. with a cross (X), deposited at base, for the cor. of secs. 19, 20, 29, and 30, with brass cap mkd.