

SUBDIVISION OF T. 19 S., R. 63 E.

Chains

West, on a true line, bet. secs. 19 and 30.

Desc. 12 ft.; over sand hills, through scattered undergrowth.

10.00 Leave sand area bearing N. and S.; desc. 48 ft. over benchland.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 16 ins. in the ground to solid rock, with a limestone, 8x8x2 ins. mkd. with a cross (X), deposited at base, and in a mound of stone, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

S19

 $\frac{1}{4}$

S30

1933

Over benchland; desc. 29 ft.

51.40 Wash, 20 lks. wide, 2 ft. deep, course SW.

60.20 Wash, 5 lks. wide, 1 ft. deep, course SW.

69.98 Intersect W. bdy. of Tp. S., 0° 34' E., 1.63 chs. dist. from the cor. of secs. 24 and 25, R. 62 E., heretofore described.

At point of intersection,

Set an iron post, 3 ft. long, 3 ins. diam., 27 ins. in the ground, for the closing cor. of secs. 19 and 30, with brass cap mkd.

T19S

R62E

R63E

S19 C

S25

S30 C

1933

of stone, 4 ft. base, 2 ft. high, E. of cor. raise a mound

Land, flat.

Soil, sand and gravel; 4th rate.

Undergrowth, creosote, buckbrush. Sand grass.

Grazing, very poor.

From the cor. of secs. 19, 20, 29, and 30.

N. 0° 03' W. bet. secs. 19 and 20.

Across flat sandy bottom, through scattered undergrowth.

13.00 Leave sand dune area, bears NE. and SW.; cross series of small washes; asc. 48 ft.

28.50 Wash, drains SW.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground to solid rock, with a cross (X) mkd. on solid rock at base, in a mound of stone, for $\frac{1}{4}$ sec. cor., with brass cap mkd.