

SUBDIVISION OF T. 19 S., R. 63 E.

Chains Tl sec	West, on a true line, bet. secs. 7 and 18.	1933
	Across rolling S. slope, through medium dense undergrowth; desc. 37 ft.	
13.60	Wash, 50 lks. wide, 4 ft. deep, course S. 30° W.; asc. 6 ft.	
20.40	Old road, bears N. and S. about 6 chs. then SW.	
39.50	Wash, course S.	
40.00	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.	38.0
	S7	1933
50.00	Wash, course S. 30° W. asc. 10 ft. 1933	38.0
54.90	Wash, course S.; across nearly level land.	38.0
58.80	Wash, 50 lks. wide, 3 ft. deep, course S.; asc. 11 ft.	38.0
69.69	Intersect W. bdy. of Tp. S. $0^{\circ} 14'$ E., 2.59 chs. dist. from the cor. of secs. 12 and 13, R. 62 E., heretofore described.	38.0
	T19S R62E S7 C S13 C S18	1933
	At point of intersection, draw mrd as for 38.0A to S13 and S18. Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, in a mound of stone, for the closing cor. of secs. 7 and 18, with brass cap mkd.	38.0A
	T19S R62E S7 C S13 C S18	1933
	From S13, go N. 45° E. 31 chs. dist. to S18. Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, in a mound of stone, 4 ft. base, 2 ft. high, E. of cor. of secs. 7 and 18, with brass cap mkd.	38.0B
	T19S R62E S7 C S13 C S18	1933
	Land, rolling S. slope. Soil, sand loam surface 3 ft. deep, gravel and rock below; 3rd rate. Undergrowth, creosote, buckbrush, yucca, desert holly, and cactus. Grazing, very poor.	38.0C
	T19S R62E S7 C S13 C S18	1933
11.80	Over rolling, broken country, through medium dense undergrowth. Draw, course S. 30° W.; asc. 38 ft.	38.0D
24.70	Old road, bears NE. and SW.	38.0D