

## SUBDIVISION OF T. 19 S., R. 63 E.

## Chains

West, on a true line, bet. secs. 6 and 7.

- Asc. 69 ft. on N. slope, through medium dense under-growth.
- 5.00 Spur, projects SE.; slope changes to SE.; asc. 72 ft.
- 7.70 Spur ridge, projects SW. from N.  $20^{\circ}$  E.; desc. W. slope along bottom of draw, course W.; desc. 12 ft.
- 17.60 Leave draw, course N.  $60^{\circ}$  W.; desc. 22 ft.; along N. slope.
- 22.60 Same draw, course S.  $60^{\circ}$  W.; asc. 20 ft.
- 24.93 Spur, projects SW.; center of hoist over incline shaft bears N.  $72^{\circ}$  E., 224 lks.; desc. 57 ft.
- 32.80 Old road, bears NE. and SW.; desc. 20 ft.
- 40.00 Set an iron post 3 ft. long, 1 $\frac{1}{2}$  in. diam., 27 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.
- $\frac{1}{4}$  —
- 47.00 Set an iron post 3 ft. long, 1 $\frac{1}{2}$  in. diam., 27 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.
- 53.30 Draw, course S.  $30^{\circ}$  W. from N.  $35^{\circ}$  E.; asc. 10 ft.
- 62.00 Spur, projects SW. from N.  $30^{\circ}$  E.
- 64.80 Wash, course S.  $30^{\circ}$  W.; asc. 17 ft.
- 69.89 Intersect W. bdy. of Tp. S.  $0^{\circ} 07'$  E., 3.31 chs. dist. from the cor. of secs. 1 and 12, R. 62 E., heretofore described.
- At point of intersection, set 3 posts in line.
- Set an iron post 3 ft. long, 3 ins. diam., 27 ins. in the ground, for the closing cor. of secs. 6 and 7, with brass cap mkd.
- T19S  
R62E R63E S6 C  
S12 S7 C 1933
- raise a mound of stone 4 ft. base, 2 ft. high, E. of cor.
- Land, rough, rolling broken foothills N.E.; rolling bottomland W.  $\frac{1}{2}$ . Soil, sand loam surface, gravel below; 3rd rate. Undergrowth, creosote, buckbrush, cactus, yucca. Sand grass. Grazing, very poor.