

## SUBDIVISION OF T. 19 S., R. 63 E.

129

## Chains

Establishment of the  $\frac{1}{4}$  sec. cor. for sec. 31,  
on the W. bdy. of T. 19 S., R. 63 E.

At midpoint between the cor. of Tps. 19 and 20 S., Rs. 62  
and 63 E. and the closing cor. of secs. 30 and 31, here-  
tofore described,

Set an iron post, 5 ft. long, 1 in. diam., 27 ins. in the  
ground, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$\frac{1}{4}$   
S31  
1933

raise a mound  
of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, E. of cor.

From this cor. the  $\frac{1}{4}$  sec. cor. of sec. 36, T. 19 S., R.  
62 E., heretofore described, bears N.  $0^{\circ}32'$  E., 0.61  
chs. dist.

Establishment of the  $\frac{1}{4}$  sec. cor. for sec. 30,  
on the W. bdy. of T. 19 S., R. 63 E.

At midpoint between the closing cor. of secs. 19 and 30  
and the closing cor. of secs. 30 and 31, heretofore  
described,

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in  
the ground, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$\frac{1}{4}$   
S30  
1933

From this cor. the  $\frac{1}{4}$  sec. cor. of sec. 25, T. 19 S.,  
R. 62 E., heretofore described, bears N.  $0^{\circ}34'$  W., 1.30  
chs. dist.

Establishment of the  $\frac{1}{4}$  sec. cor. for sec. 19,  
on the W. bdy. of T. 19 S., R. 63 E.

At midpoint between the closing cor. of secs. 18 and 19  
and the closing cor. of secs. 19 and 30, heretofore  
described,

Set an iron post, 3 ft. long, 1 in. diam., 14 ins. in  
the ground to solid rock, in a mound of stone, for  $\frac{1}{4}$   
sec. cor., with brass cap mkd.

$\frac{1}{4}$   
S19  
1933

A rock 10x8x2 ins., mkd. with a cross (X) deposited at  
base of post.

From this cor. the  $\frac{1}{4}$  sec. cor. of sec. 24, T. 19 S.,  
R. 62 E., heretofore described bears N.  $0^{\circ}09'$  W., 1.93  
chs. dist.